

MS56A-4 0,06KW 230/400V B14

Three-phase asynchronous motor in aluminum

Motor type MS56A-4 0,06KW 230/400V B14
 Brand BUSCK
 Item number 03040563

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,06	50	0,52	1400
400	0,06	50	0,30	1400
460	0,07	60	0,30	1680

Duty	S1	Efficiency class	IE1
Enclosure	IP55	Efficiency, load 100%	52,8
Insulation class	F	Efficiency, load 75%	47,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	38,7
Max. ambient temp.	40°C	Power fact, load 100%	0,55
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	2,9
Torque, Nm	0,40	Sound pressure Lp dB(A)	50
Starting torque ratio	3,1	Bearing DE	6201-2Z/C3
Pull up torque ratio	3	Bearing NDE	6201-2Z/C3
Pull out torque ratio	3,2	Balance grade	Normal
Starting current ratio	4	Inertia kgm ²	0,00019
		Cable entries	1xM16

