

T2A56C-4 0,12KW 230/400V B5

Three-phase asynchronous motor in aluminum

Motor type T2A56C-4 0,12KW 230/400V B5
Brand BUSCK
Item number P3040562e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,12	50	0,83	1375
400	0,12	50	0,48	1375
460	0,14	60	0,48	1650

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 45°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 0,83
Starting torque ratio 3,3
Pull up torque ratio 2,8
Pull out torque ratio 3,2
Starting current ratio 3,6
This motor has DNV type approval

Efficiency class IE2
Efficiency, load 100% 59,1
Efficiency, load 75% 57,5
Efficiency, load 50% 51,4
Power fact, load 100% 0,61

Painting Standard
Color RAL 9005
Weight kg 3,91
Sound pressure Lp dB(A) 52
Bearing DE 6201-2Z/C3
Bearing NDE 6201-2Z/C3
Balance grade Normal
Inertia kgm² 0,00029
Cable entries 1xM20

