

T3A100LB-4 3KW 230/400V B34


Three-phase asynchronous motor in aluminum

Motor type T3A100LB-4 3KW 230/400V B34
Brand BUSCK
Item number 93041015

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	3	50	10,96	1450
400	3	50	6,3	1450
460	3,45	60	6,3	1740

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	87,7
Insulation class	F	Efficiency, load 75%	88
Cooling	IC411 (TEFC)	Efficiency, load 50%	86,9
Max. ambient temp.	40°C	Power fact, load 100%	0,78
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	28,3
Torque, Nm	19,76	Sound pressure Lp dB(A)	64
Starting torque ratio	3,3	Bearing DE	6206-2Z/C3
Pull up torque ratio	2,7	Bearing NDE	6206-2Z/C3
Pull out torque ratio	3,4	Balance grade	Normal
Starting current ratio	8,1	Inertia kgm ²	0,0096
Winding protection	Thermocontacts	Cable entries	1xM20, 1xM16

Note IE3, Termokontakter



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no