

T3A112M-4 4KW 400/690V B5

Three-phase asynchronous motor in aluminum

Motor type T3A112M-4 4KW 400/690V B5
Brand BUSCK
Item number 93041122


Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	4	50	7,9	1450
690	4	50	4,54	1450
460	4,6	60	7,9	1740

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 26,34
Starting torque ratio 3,1
Pull up torque ratio 2,6
Pull out torque ratio 3,7
Starting current ratio 8,6
Balance grade Normal
Inertia kgm2 0,0152916
Winding protection Thermocontacts

Efficiency class IE3
Efficiency, load 100% 88,6
Efficiency, load 75% 88,8
Efficiency, load 50% 88,2
Power fact, load 100% 0,82

Painting Standard
Color RAL 9005
Weight kg 32
Sound pressure Lp dB(A) 65
Bearing DE 6306-2Z
Bearing NDE 6206-2Z
Cable entries 2xM25, 1xM16



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no