

T3A80B-2 1,1KW 230/400V B3


Three-phase asynchronous motor in aluminum

Motor type T3A80B-2 1,1KW 230/400V B3
Brand BUSCK
Item number 93020811

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	1,1	50	4,07	2900
400	1,1	50	2,34	2900
460	1,27	60	2,34	3480

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	82,7
Insulation class	F	Efficiency, load 75%	82,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	79,9
Max. ambient temp.	40°C	Power fact, load 100%	0,83
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	10,6
Torque, Nm	3,63	Sound pressure Lp dB(A)	67
Starting torque ratio	3,2	Bearing DE	6204-2Z/C3
Pull up torque ratio	2	Bearing NDE	6204-2Z/C3
Pull out torque ratio	3,4	Balance grade	Normal
Starting current ratio	8,7	Inertia kgm ²	0,00127
Winding protection	Thermocontacts	Cable entries	1xM20

Note IE3, Termokontakter



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no