

T3A90S-4 1,1KW 230/400V B35

Three-phase asynchronous motor in aluminum

Motor type T3A90S-4 1,1KW 230/400V B35
Brand BUSCK
Item number 93040904


Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	1,1	50	4,43	1440
400	1,1	50	2,55	1440
460	1,27	60	2,55	1728

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 7,3
Starting torque ratio 3,7
Pull up torque ratio 3,1
Pull out torque ratio 3,8
Starting current ratio 7,7
Balance grade Normal
Inertia kgm² 0,00384
Winding protection Thermocontacts

Efficiency class IE3
Efficiency, load 100% 84,1
Efficiency, load 75% 84,1
Efficiency, load 50% 81,8
Power fact, load 100% 0,74

Painting Standard
Color RAL 9005
Weight kg 15
Sound pressure Lp dB(A) 61
Bearing DE 6205-2Z
Bearing NDE 6205-2Z
Cable entries 1xM20, 1xM16



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no