

T3AB80B-4 0,75KW 230/400V B5

Three-phase asynchronous brake motor in aluminum

Motor type T3AB80B-4 0,75KW 230/400V B5
Brand BUSCK
Item number B3040812e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,75	50	3,13	1430
400	0,75	50	1,8	1430
460	0,86	60	1,8	1716

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Efficiency class IE3
Efficiency, load 100% 82,5
Efficiency, load 75% 83
Efficiency, load 50% 81,1
Power fact, load 100% 0,73

Painting Standard
Color RAL 9005
Weight kg 13,61
Sound pressure Lp dB(A) 58
Bearing DE 6204-2Z/C3
Bearing NDE 6204-2Z/C3
Balance grade Normal
Inertia kgm2 0,002284565

Torque, Nm 5,01
Starting torque ratio 2,7
Pull up torque ratio 2,3
Pull out torque ratio 2,8
Starting current ratio 6,1

Note Brake motor IE3 Brake torque, Nm 12

